

P.O. BOX 3786, BRACKNELL, BERKS, RG12 7TH
TELEPHONE: 0118 989 2666 FAX: 0118 989 0929
E-MAIL: sales@dichem.co.uk
WEB: www.dichem.co.uk



1. Identification of the Substance/Preparation & Supplier.

Supplier: Direct Chemicals, PO BOX 3786, Bracknell, Berkshire, RG12 7TH
Tel. 0118 989 2666 Fax: 0118 989 0929

Product Name: Tuffacure R90

Product Type: Resin Based Curing agent and Sealer for Concrete

2. Hazards Identification.

Hazard designation:

F Flammable

Xn Harmful

N Dangerous for the Environment

Information pertaining to particular dangers for man and environment:

R10: Flammable

R65: Harmful: may cause lung damage if swallowed

R66: Repeated exposure may cause skin dryness or cracking

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Classification system:

The health and environmental hazards of this preparation have been assessed by the conventional method described in annex II and III of the preparations Directive 1999/45 EC.

3. Composition/Information on Ingredients.

Dangerous components:

Hazardous component:	EINECS	Cas No.	Index	Risk Phrases:	Concentration:
Petroleum Distillate	265-185-4	64742-82-1	F	R10,R65,R66,R51/53	60-100%

Additional information: For the wording of the listed risk phrases refer to section 16.

4. First Aid Measures.

Immediate medical attention is required.

Eye Contact: Flush with clean water for 15 minutes. If irritation persists, obtain medical attention.

Skin Contact: Remove contaminated clothing. Wash off with soap and water. The application of skin reconditioning (emollient) cream, can be beneficial.

Inhalation: Remove to fresh air. If symptoms persist, seek medical advice.

Ingestion: Water to drink and rinse may be beneficial. **Aspiration Hazard. May cause rapid absorption via lungs, resulting in injury to other body systems. Do not induce vomiting without medical advice.**

5. Fire Fighting Measures:

Suitable Extinguishing Media: Foam, Dry Powder, Co2, Sand, Earth, Fine Water Spray suitable.

Unsuitable Extinguishing Media for Reasons of Safety: Water Jet.

Special Hazards caused by the material, its products of combustion or flue gases: Classed as flammable. If involved in fire, may evolve noxious fumes. Fire exposed containers should be sprayed with water to keep cool and avoid bursting.

Protective Equipment: Self-contained breathing apparatus may be required.

P.O. BOX 3786, BRACKNELL, BERKS, RG12 7TH
TELEPHONE: 0118 989 2666 FAX: 0118 989 0929
E-MAIL: sales@dichem.co.uk
WEB: www.dichem.co.uk



6. Accidental Release Measures.

Personal safety precautions: Remove ignition sources. Wear protective equipment. Keep unprotected persons away. Use protective clothing, chemical eye goggles and PVC or rubber gloves.

Measures for environmental protection: Prevent from spreading (e.g. by dusting a ring of chemical binder). As the product is hazardous for the aquatic environment, it must be prevented from reaching surface water. Inform authorities in case of contamination of water or sewage system.

Methods for cleaning/collecting: Soak liquid in absorbent material and collect solids in a container. Wash down floor area as spillages can be slippery. Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent. Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product. Use only in well ventilated areas.

7. Handling and Storage.

Handling:

Information for safe handling: Keep in tightly closed containers. Take note of emission threshold.

Storage:

Requirements to be met by storerooms and containers: Store between 0-35°C. Store in mild steel, stainless steel or polyethylene containers.

Information about storage in a common storage facility: Store in a cool dry place away from heat or sources of combustion.

Specific Uses: To be used as a Protective Coating.

8. Exposure Controls/Personal Protection.

Exposure limit values:

Ingredient Name	8hr TWA	15min STEL
Petroleum Distillate WEL	600mg/m ³	

EH40 guidance on exposure to mixed solvents.

Occupational exposure controls:

Respiratory Protection: Unlikely to be necessary. Avoid breathing vapours.

Hand: PVC or rubber gloves are recommended.

Eyes: Safety eye goggles should be worn.

Skin: Use protective clothing. Remove contaminated clothing and wash with soap and water.

Environmental exposure controls:

Dispose only in accordance with Local Authority regulations, via authorised waste disposal agent.

P.O. BOX 3786, BRACKNELL, BERKS, RG12 7TH
TELEPHONE: 0118 989 2666 FAX: 0118 989 0929
E-MAIL: sales@dichem.co.uk
WEB: www.dichem.co.uk



9. Physical and Chemical Properties.

Appearance:	Clear, Pale Yellow Fluid
Odour:	Solvent
Boiling Range:	150-200°C
Flash Point:	38°C
Flammability:	Flammable
Explosive Limits:	0.9 – 8.0%
Vapour Pressure:	0.44 kpa @ 20°C
Solubility:	Soluble in many solvents
Water Solubility:	Immiscible
Viscosity @ 40°C:	3.0c/st
Vapour Density:(Water=100)	>1
Solubility in Organics	Soluble in many
Freezing Point	<0°C
Auto Ignition Temp	230°C
Specific Gravity @ 20°C	0.800 typical

10. Stability and Reactivity.

Conditions to Avoid: Protect against naked flames, hot surfaces and other high temperature sources.

Materials to Avoid: Strong oxidising agents.

Hazardous Decomposition Products: Oxides of carbon, water vapour and unidentified organic and inorganic compounds, some of which may be toxic may be produced. Product is stable under normal conditions.

11. Toxicological Information.

Eyes:	May give rise to irritation and stinging.
Skin:	Prolonged or repeated contact may lead to de-fatting of the skin and/or slight irritation.
Inhalation:	Excessive exposure to mists caused by atomising systems may cause irritation to eyes and respiratory tract.
Ingestion:	Aspiration Hazard. May cause lung damage if material gets into lungs after swallowing, breathing vapour/spray or vomiting swallowed material. Swallowing of small amounts is not likely to cause serious discomfort. If swallowed in larger quantities may cause vomiting and diarrhoea.

12. Ecological Information.

Ecotoxicity: Expected to be toxic to aquatic organisms, long-term adverse effects not expected.

Mobility: The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. Avoid transfer into the environment.

Persistence and Degradability: Product biodegrades slowly.

Bio-accumulative Potential: Not expected to bio-accumulate.

13. Disposal Recommendations.

Product should be disposed of via an authorised waste disposal contractor in accordance with all local and national regulations.

Dispose of empty containers in accordance with local and national regulations.

Advice can be obtained from the Waste Regulation Authority whether special waste regulations apply to this product.

P.O. BOX 3786, BRACKNELL, BERKS, RG12 7TH
 TELEPHONE: 0118 989 2666 FAX: 0118 989 0929
 E-MAIL: sales@dichem.co.uk
 WEB: www.dichem.co.uk



14. Transport Information.

UN Label:



Land Transport ADR/RID:

UN No:	1268	Tremcard:	30G35
Class:	3	HI No:	30
Proper Shipping Name:	Petroleum Distillates NOS	ADR Classification Code:	F1
Packing Group:	III	Limited Quantities Code:	LQ7
Marine Pollutant:	Yes		

Maritime Transport IMDG:


UN No:	1268	Tremcard:	30G35
Class:	3	HI No:	30
Proper Shipping Name:	Petroleum Distillates NOS	EmS No:	3-07, F-E, S-E
Packing Group:	III		
Marine Pollutant:	Yes		

15. Regulatory Information.

Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (CHIP).

Hazard Symbol:



F	Flammable
Xn	Harmful
N	Dangerous for the Environment

Risk Phrases:

R10:	Flammable
R65:	Harmful: may cause lung damage if swallowed
R66:	Repeated exposure may cause skin dryness or cracking
R51/53:	Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

Safety Phrases:

S23:	Do not breathe vapour or spray
S37:	Wear suitable gloves
S43:	In case of fire use foam/dry powder/CO2 – fine water spray suitable
S51:	Use only in well ventilated areas
S62:	If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label.
S24/25:	Avoid contact with skin and eyes

P.O. BOX 3786, BRACKNELL, BERKS, RG12 7TH
TELEPHONE: 0118 989 2666 FAX: 0118 989 0929
E-MAIL: sales@dichem.co.uk
WEB: www.dichem.co.uk



National Regulations:

Regulations which may apply in event of accident:

Control of Major Accident Hazards (COMAH)

Critical quantity values according to the regulations on accidents should be adhered to.

16. Other Information.

Do not mix with other chemicals.

The information provided in this data sheet has been compiled in accordance with the requirements of the Chemicals (Hazard information and packaging) Regulations, Directive 93/112/EC, as amended.

This data sheet does not constitute an assessment of the workplace risks as required under the provisions of the Health & Safety at Work act and the Control of Substances Hazardous to Health (COSHH).

R-phrases relevant to the products hazardous ingredients:

R10: Flammable

R65: Harmful: may cause lung damage if swallowed

R66: Repeated exposure may cause skin dryness or cracking

R50/53: Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment

Training Advice:

Further information under the regulations of use can be taken from the Product Data Sheet. Should you require any information regarding classification and registration of preparations containing this product please contact our Regulatory Department, Tel 0118 989 2666

Recommended Restrictions on Use:

Department issuing data specification sheet: Health and Safety Department

Contact: Robin Wells

*Date compared to the previous version altered.

Legal Disclaimer:

The information supplied above is based upon the present state of our knowledge of the product at the time of publication. It is given in good faith and no warranty is implied with respect to the specification or quality of the product. The user must satisfy himself that the product is entirely suitable for his purpose.