

FORMEASE CRA1



Concrete Chemical Release Agent BCA (C&CA) Category 5

DESCRIPTION

FORMEASE CRA1 is a slower drying type chemically active release agent formulated to give easy release of formwork and quality surface finishes to concrete. **FORMEASE CRA1** is suitable for use with many form liner systems, Steel forms and most other Form Materials. Due to its Non-Flammable and low odour properties this product is the preferred release agent in enclosed environments such as pre-cast factories, tunnels and basements

ADVANTAGES

- Suitable for use on all types of formwork and is the preferred type of product on proprietary MDO & HDO plywood forms and steel shutters, it can also be used on sealed timber forms .
- A low viscosity liquid which is easily sprayed through fine sprays without clogging
- Economic coverage rates can be obtained using spray equipment, with coverage costs averaging no more than a few pence per m² on steel forms .
- The high quality raw materials allow the product to be used at low temperatures, unlike low quality gas oil derived blends.
- Can be applied just prior to casting, or pre-treated forms may be let until dry. Treated forms can be exposed to the environment for 14 days without re-treatment
- Once dry soffit shutters can be walked on safely. This takes 2-3 hours
- Provides a quick, positive release of formwork, reducing labour costs and damage to formwork and moulds.
- Greatly reduces the occurrence of blowholes, surface blemishes and staining.

PROPERTIES

| | |
|-------------------|----------------------------------|
| Appearance: | Clear light straw, low viscosity |
| Specific Gravity: | 0.85 @ 20°C |
| Flash Point: | 75°C |
| Viscosity: | >7.0c/st |
| Freezing Point: | <0°C |
| Storage Life: | Indefinite in sealed drums |
| VOC Content: | 80g/litre |

COVERAGE

25 to 60m²/litre dependent on type of form, porosity, texture of surface and ambient temperature.

| | |
|--------------------------|----------------------------|
| Plywood: | 25-30m ² /litre |
| MDO & HDO Plywood: | 30-40m ² /litre |
| Plastic Coated Plywoods: | 40-60m ² /litre |
| Metal, Fibreglass: | 40-60m ² /litre |

APPLICATION

FORMEASE CRA1 is ready for use and should not be diluted. It should be applied as thinly and evenly as possible for optimum performance onto clean and dry surfaces.

It can be applied to all types of formwork by spray, or absorbent applicator. Any excess should be mopped up. For the best and most economical performance, application by mist spray is recommended. Excellent results can be obtained using a Gloria 410T or Mesto Ferro Plus Sprayer with an 8001 tip fitted.

Many new forms are not factory treated with oils, so for new or 'unsealed' timber formwork, pre-treatment is essential with two coats prior to use. This will extend the useful life of the form and help to standardise surface absorbency.

STORAGE & HANDLING

FORMEASE CRA1 in manufacturer's sealed drums requires no special storage facilities

Material should be applied in well ventilated areas.

Keep away from naked flames, electrical equipment, foodstuffs and children.

Storage life is indefinite in sealed drums.

PACKAGING & TRANSPORT

FORMEASE CRA1 is supplied in 25ltr, 205ltr Drums & 1000ltr IBCs.

Not Regulated for Road Transport.

HEALTH & SAFETY

Refer to separate safety data sheet. Copies available on request.

If spraying, care should be taken to minimise inhalation and contact with eyes and ensure adequate ventilation during application.

QUALITY ASSURANCE

Direct Chemicals Ltd is a firm of assessed capability. The Company's quality system conforms to BS EN ISO 9001:2008 and is assessed by QMS International PLC. Products are manufactured under quality assured schemes

Direct Chemical Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Direct Chemicals Ltd Terms and Conditions of Sale, copies of which are available on request. Direct Chemicals Ltd endeavors to ensure that the above data and any further advice is correct, however Direct Chemicals Ltd can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not override the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

Rev 3, 06.15
Page 1 of 1

Direct Chemicals Ltd
Unit 6, Stokes Farm, Binfield Rd,
Wokingham, Berkshire, RG40 5PR

Tel: 0118 989 2666
sales@dichem.co.uk
dichem.co.uk