

# EDGESEAL PU1K

Solvent based, blue tinted, one part polyurethane sealer for sawn edges of formwork

## DESCRIPTION

**EDGESEAL PU 1K** is a blue tinted, penetrative, solvent borne one part polyurethane sealer specifically developed for the concrete industry to seal cut and exposed edges on all types of formwork ply or to treat any holes cut for tie rods etc. It is principally used to extend the life of formwork panels by stopping water absorption and longer term de-lamination along any cut edges. It is capable of being applied to damp timber or timber with high moisture levels, unlike solvent borne systems.

Factory produced boards are generally edge sealed in the production cycle and The Council of Forest Industries (COFI) and Finnish Plywood International, both recommend proper sealing of cut edges in plywood to extend form life and minimise any swelling and edge distortion.

## ADVANTAGES

- Greatly extends mould and formwork life by sealing of exposed edges to water absorption and de-lamination.
- Standardises surface absorption therefore vastly reduces the effect of hydration variation staining appearing on the concrete.
- Specifically formulated to comply with recommendations from ply manufacturers so that site or factory engineers can see the coloured edges have been sealed in the correct manner.
- Single pack, product for easy application by brush, or roller.
- Resistant to formwork chemical release agents, mould oils, retarders and alkali cement.
- Can be applied successfully to damp timber.
- Will not impair the bond of paints, plasters, coatings, etc when used with the correct type of release system.

## PROPERTIES

Appearance:	Opaque Blue, brushing consistency
Flash Point:	40°C
Freezing Point:	<0°C
Storage Life:	1 Year stored above 5°C
Mechanical Cure:	24 hours
Full Chemical Cure:	72 hours
U.V Stable:	No - will yellow

## COVERAGE

6-10m<sup>2</sup> per litre, but is very dependant on surface porosity and profile.

### Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR  
Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)

## APPLICATION

Surfaces to be treated should be clean, previously untreated with paints, oils etc. Surface moisture levels should be kept to a minimum, however, **EDGESEAL PU 1K** has moisture tolerance properties, but if in doubt conduct a trial patch to test satisfactory cure and adhesion.

Application should **not** be carried at temperatures below 5°C or where the temperature will fall below this before the coating as dried sufficiently.

**EDGESEAL PU 1K** is supplied ready for use, **DO NOT DILUTE**.

Normally only one or two coats is all that is required to ensure water repellency, this should be applied liberally but evenly to the areas requiring treating.

All tools and equipment can be cleaned with a suitable solvent cleaner.

Treated forms need protection from rain, temperatures below 5°C and dust for a number of hours after treatment.

Forms can be used after 24 hours drying.

## STORAGE & HANDLING

Protect from temperatures below 5°C Store in accordance with Health and Safety regulations for flammable liquids. Keep away from naked flames and children. Keep containers sealed when not in use.

## HEALTH & SAFETY

Refer to separate material safety data sheet. Copies available by request

## PACKAGING & TRANSPORT

Supplied in 5ltr metal screw top drums. Regulated for Road Transport. LQ

## QUALITY ASSURANCE

Norsekem Limited Products are manufactured under quality assured schemes

Norsekem Limited products are guaranteed against defective materials and manufacture. Products are sold subject to the Norsekem Limited Terms and Conditions of Sale, copies of which are available on request. Norsekem Limited endeavors to ensure that the above data and any further advice is correct, Norsekem Limited can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.

## Norsekem Limited

Unit 6c, Stokes Farm, Binfield Road, Wokingham, Berkshire. RG40 5PR

Tel: 08454027663 Fax: 0845 4027662 Email: sales@norsekem.co.uk

[norsekem.co.uk](http://norsekem.co.uk)