

AGGREGATE Wet & Dry 6mm & 10mm

Product Codes

TM06, TM07, TM26 & TM27 Packaging listed below

Description

Aggregate supplied by Parex have been specially selected for grading and shape. The stone type is silica with a high degree of purity. All Aggregate types are continuously graded and are washed clean.

Aggregates are used to bulk out both cementitious and resin based products where thick section applications are required. When used with cementitious mixes the wet or dry types may be used. When used with resin based mixes only the dry type of aggregate must be used. The selection of 6mm or 10mm maximum sized stone will depend on the particular job being undertaken.

Uses Include: Bulking out of cement based grouts and mortars.
Bulking out of polyester and epoxy resin based grouts and mortars.

Typical Properties

Appearance	Rounded stone White and brown colour
Chemical composition Silica (as SiO₂)	95% minimum
Density	2650 kg/m ³
Moh's Hardness	6 to 7

Standards

Aggregates have been tested in accordance with the appropriate parts of EN 12620.

Specification Outline

Bulk filling of cement based mixes or resin based mixes for thick section applications shall be carried out using Aggregate as supplied by Parex Ltd. The Aggregate must be stored, handled and used strictly in accordance with the manufacturer's instructions.

Quality Assurance

Parex Ltd is a firm of Assessed Capability. The Company's quality system conforms to BS EN ISO 9001:2008 and is assessed by UK CARES LTD.

Instructions For Use

The instructions for use given for the particular product in use must be followed when bulking out of the product is undertaken.

Precautions

Health and Safety

The precautions given for the given for the particular product in use must be followed when bulking out of the product is undertaken.

Full health and safety data are given in Product Safety Data Sheets for the particular products being used.

Fire

Aggregates are non-flammable

Yield

Aggregates are packed in 25kg bags. Each 25kg bag addition will increase the yield of the particular product being used by approximately 9½ litres.

Storage And Shelf Life

Aggregates stored in unopened bags under clean dry conditions will have an indefinite shelf life.

Packaging And Ordering

Aggregates are supplied in 25kg bags.
25kg Bags 6mm Wet Product Code TM 06
25kg Bags 10mm Wet Product Code TM 07
25kg Bags 6mm Dry Product Code TM 26
25kg Bags 10mm Dry Product Code TM 27

For further information and sales please contact your local Parex Office as listed below.

Parex Ltd products are guaranteed against defective materials and manufacture. Products are sold subject to the Parex Ltd Terms and Conditions of Sale, copies of which are forwarded on invoice and are available on request. Parex Ltd endeavours to ensure that the above data and any further advice is correct, however, it cannot accept any direct or indirect liability for the use of its products as such usage is beyond its control.