



Pieri® DPL RB Classic

(formerly RB 200)

Construction Joint Formwork Retarder

Description

An economical formwork surface retarder for production of construction joints or roughened key surfaces on concrete.

Applications

Pieri® DPL RB Classic can be used on most types of form surface but it must be free of grease. Use of Pieri DPL RB Classic allows for delayed stripping for several days as long as the formwork is not removed from the retarded concrete.

After stripping the concrete, mould cleaning by washing is recommended.

With Pieri DPL RB Classic the depth of retardation varies according to the thickness it is applied – so it must not be used for façade or decorative concrete work (see our Data Sheets on Pieri DRC 6 series retarders for architectural quality finishes).

Directions for use

Shake or stir the drum thoroughly before use.

Apply to the formwork surface with a brush or roller and allow to dry – approximately 15 minutes. Pieri DPL RB Classic, once hardened forms an abrasive resistant film for both vertical and horizontal concrete work. After stripping from the formwork brush or wash off all the deactivated residues to ensure full bond of subsequent coatings or concretes.

N.B. For top face retardation in construction joint work use Pieri® Top.

Technical Specifications

- Partially volatile and flammable product (flash point 6° C, SETAFLASH method)).
- Density : approx 1.03.
- Coverage: 6 - 8 m²/litre.
- Not sensitive to freezing conditions.
- Viscosity : approx. 15 to 30 seconds, AFNOR cup n°4 at 20°C.

Storage

18 months in original unopened packaging.

Packaging

20 litre drum.

Safety

Flammable
Please consult our material Safety Data Sheet.

Transport

- UN N° : 1263.
- Class : 3.2.

Web Visit our web site at: www.graceconstruction.com

Grace Construction Products 852 Birchwood Boulevard, Birchwood, Warrington, Cheshire WA3 7QZ England. Tel: (01925) 824824 Fax: (01925) 824033

Pieri is a registered trademark of W R Grace & Co.-Conn.

We hope information here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would infringe any patent or copyright. Grace Construction Products Limited, 852, Birchwood Boulevard, Birchwood, Warrington, WA3 7QZ, Cheshire, England.

This product may be covered by patents or patents pending. Copyright 2005 W. R. Grace & Co.-Conn.

PIERI023

Printed in UK - 02/05

GRACE
Construction Products