

Thin Section Foam Tape for Grout loss Prevention in Formwork

DESCRIPTION

A firm, high density foam PVC sealant coated on one side with a strong acrylic pressure-sensitive adhesive.

In its standard size it is ideal for sealing the base of shutters against grout loss, being very thin it will leave little or no rebate to make good once the shutter has been removed.

ADVANTAGES

- 30% compression assures grout tight seal
- Effective vibration damping
- Suitable for heavy duty metal to metal sealing
- Resists oxygen, weather, fungi
- Liner prevents stretch during application
- Abrasion resistant
- Rolls do not fall apart during application

PROPERTIES

Colour:	Black
Hardness:	47 Shore 00
Force to Compress:	5.5 N/cm ²
Compression Deflection:	3.0 N/cm ²
Compression Set:	10% Maximum
Water Absorption:	5% Maximum
Minimum Application Temperature:	5°C
Temperature Resistance:	-30 to ±70°C

Application

It is essential, as with all pressure sensitive tapes, that the surfaces to which the tape is applied be clean, dry and free of grease and oil.

COVERAGE

Not applicable.

STORAGE & HANDLING

No special storage facilities are needed.

PACKAGING & TRANSPORT

Rolls of 1.5mm thick x 12mm wide x 60m long.

Packed 25 rolls to the box.

Not regulated for Road Transport

HEALTH & SAFETY

Not Regulated

QUALITY ASSURANCE

Direct Chemicals is a firm of assessed capability. The Company's quality system conforms to BS EN ISO 9001:2000 and is assessed by QMS International PLC. Products are manufactured under quality assured schemes



Direct Chemical products are guaranteed against defective materials and manufacture. Products are sold subject to the Direct Chemical Terms and Conditions of Sale, copies of which are available on request. Direct Chemicals endeavours to ensure that the above data and any further advice is correct, however Direct Chemicals can not accept liability for the use to which products are put or the way in which they are used. All recommendations stated by the company are made in good faith. Recommendations do not over-ride the basic obligation of the user to satisfy themselves at all times as to suitability of the product for their particular application.



Direct Chemicals
PO BOX 3786, Bracknell
Berkshire, RG12 7TH
Tel: 0118 989 2666
Fax: 0118 989 0929
Email: sales@dichem.co.uk
Web: www.dichem.co.uk

